TAPES & ADHESIVES

DOUBLE-SIDED POLYESTER FILM TAPE

- · Ideal for general mounting and holding
- Polyester film coated on both sides with a high shear strength adhesive; silicone paper liner
- Ideal for carpet laying, trophies, mouldings and picture frames
- Bonds to paper, foil and plastic film
- 180' (55 m) per roll
- Thickness: 6.5 mils



Priced per Roll

Model No.	Width	Rolls /Case	Price/Each
PE826	24 mm (1")	48	
PE827	48 mm (2")	24	

DOUBLE-SIDED PAPER TAPE

- Made of thin kraft and rope fibre tissue, coated on both sides with an aggressive high shear strength adhesive; silicone paper liner
- Features include thinness and ease of application
- 108' (33 m) per roll
- Thickness: 5 mils



Priced per Roll

Model No.	Width	Rolls /Case	Price/Each
PA677	12 mm (1/2")	72	
PA678	24 mm (1")	36	
PA679	48 mm (2")	24	

VINYL TAPE 471

- Ideal for many colour coding, abrasion protection, sealing, patching, splicing, wrapping and general purpose applications
- For use around fire extinguishers , electrical equipment
- 33 m (36 yards) per roll



3M

Model No.	Width	Colour	Rolls /Case	Price /Eacl
PC589	1/2" (12 mm)	Red	72	
PC590	1/2" (12 mm)	Blue	72	
PC591	1/2" (12 mm)	Yellow	72	
PC592	1/2" (12 mm)	White	72	
AMC510	3/4" (18 mm)	Red	48	
AMC461	3/4" (18 mm)	Blue	48	
AMC547	3/4" (18 mm)	Yellow	48	
AMC533	3/4" (18 mm)	White	48	

DOUBLE COATED POLYETHYLENE FOAM TAPE 4466

- 1/16", thick closed cell polyethylene foam carrier
- Polyethylene foam carrier
 High tack rubber adhesive
- 3.0-mils, densified kraft liner
- Temperature and environmental resistant
- · Colour: White



3M

Model No.	Dimensions	Rolls/Case	Price/Each
PB921	1/2" x 36 yds.	18	

SCOTCH® ATG ADHESIVE APPLICATORS

- Pressure sensitive two-way adhesive can be applied exactly where needed
- Ideal for mounting, splicing or bonding
- Can be used in a broad range of industries, including printing, furniture manufacturing, electronics, appliances, signs and displays, automotive and others
- ATC system applies 2-mils reinforced clear acrylic adhesive and simultaneously rewinds the tape liner inside the dispenser

Model No. PA974 Mfg. No. ATG-700 Price/Each \$

TAPE

				•
Model No.	Mfg. No.	Description	Rolls /Case	Price /Each
PA612	924-12	1/2" x 108' Tape	72	
PA613	924-19	3/4" x 108' Tape	48	

TEFLON TAPE

WATER LINES THREADS

- Provides fast positive seal for water
- lines, sewage, and sprinkler systems

 Effective on metal or plastic threads
- 3-mils thick, density 1.35-1.50
- grams/cubic centimetre

 Complies with MIL-T-27730A
- Colour: Pink

GAS LINES THREADS

- Especially for natural gas, propane, butane, water, oil and chemical lines
- 4-mils thick, density 1.35-1.50 grams/cubic centimetre
- Complies with MIL-T-22230A (ASG), UL 31 RO, AGA 3226 and CAN/ULC-S642
- · Colour: Yellow





Priced per Roll

Model No.	Dimensions"	Colour	Rolls/Case	Price /Each
PD095	1/2 x 260	Pink	50	
AG605	1/2 x 260	Yellow	100	

TEFLON THREAD SEALANT TAPE

- For use in sealing threaded pipe joints
- Non-toxic composition suitable for solvents, chemicals, oxygen and on food lines
- Permits easy disassembly even
- after years of service
 Works under pressures up to 10 000 PSI and



<u>Markal</u>





Priced per Roll

Model No.	Dimensions"	Rolls /Case	Price/Each
PA684	1/2 x 520	144	
PA685	3/4 x 520	144	

TEFLON SEALING TAPE

- Commonly used in plumbing for sealing pipe threads
- Ensures a tight seal
- · Works for both water and air
- Colour: White

Priced per Roll

- Tape Material: PTFE
- Thickness: 3 mils (0.0762mm)
- Density: 0.37 grams/cubic centimeterWorking Temperatures Range:
- Working Temperatures Range: -190°C to 260°C (-310°F to 500°F)



Model No.	Dimensions	Price/Each
PG148	1/2 x 520	
PG149	3/4 x 520	



aurora