



## KNOT WIRE WHEEL BRUSHES

- The individual knot wire tufts of a knot wheel provide minimal flexibility for more aggressive brushing action
- Rugged knot-type construction provides high brush flexibility, more uniform results, maximum safety and efficient operation at high speeds
- Brushes larger than 6" should be mounted on stationary tables; those 6" and smaller can be mounted to stationary installations or attached to portable tools


### STANDARD TWIST KNOT

- Aggressive, high impact action for severe application,
- To be used with straight grinders, bench and pedestal grinder or right angle grinder



### STRINGER BEAD

- Tighter knot, fit into more recessed area
- To be used with straight grinders or right angle grinder



There are other wheel sizes, wire sizes & arbor sizes available for all brush types.

Different materials are also available.

### STRINGER BEAD

- Small width allows this brush to be used in recessed area such as welding junctions
- **Application:** Cleaning stringer bead welds



Model No.	Brush Dia."	Arbor Hole	Wire Gauge"	Trim Length"	Face Width"	Max RPM	Price /Each
<b>STEEL</b>							
BX338	4 7/8	5/8"-11NC	0.02	1	3/16	12 000	
BX161	6 1/2	5/8"-11NC	0.02	1 1/4	3/16	12 000	
<b>STAINLESS</b>							
BX270	4 7/8	5/8"-11NC	0.02	1	3/16	12 000	
BX273	6 1/2	5/8"-11NC	0.02	1 1/4	3/16	12 000	

### HIGH SPEED STEEL SMALL GRINDER, STRINGER BEAD

- Works aggressively, smoothly and efficiently on air or portable power tools
- **Application:** Bead scale removal



Model No.	Brush Dia."	Arbor Hole	Colour	Wire Gauge"	Trim Length"	Max RPM	Price /Each
<b>STEEL</b>							
BX288	4	5/8"-11NC	Steel	0.02	7/8	20 000	
BX284	4	M-14 x 2.0	Red	0.02	7/8	20 000	
<b>STAINLESS STEEL</b>							
BX311	4	5/8"-11NC	Steel	0.02	7/8	20 000	

### STANDARD TWIST KNOT WITH 1/4" SHANK

- Designed to operate at high speeds
- **Applications:** Maintenance and metal surface cleaning



Model No.	Brush Dia."	Wire Gauge"	Trim Length"	Max RPM	Price /Each
<b>STEEL</b>					
BX193	3	0.014	5/8	25 000	
BX196	4	0.014	7/8	20 000	
<b>STAINLESS</b>					
BX195	3	0.014	5/8	25 000	
BX198	4	0.014	7/8	20 000	

### STANDARD TWIST KNOT

- **Application:** Removal of rubber flash, paint slag, scale, rust, surface contamination, weld cleaning, blending, finishing, deburring, descaling, pipeline cleaning and general cleaning



Model No.	Brush Dia."	Arbor Hole	Wire Gauge"	Trim Length"	Face Width"	Max RPM	Price /Each
<b>STEEL</b>							
BX125	4	3/8"	0.014	7/8	5/16	20 000	
BX137	6	5/8"-11NC	0.025	1 1/2	1/2	9 000	
BX144	8	5/8"	0.025	1 11/16	5/8	8 500	
<b>STAINLESS</b>							
BX202	4	3/8"	0.014	7/8	5/16	20 000	
BX272	6	5/8"-11NC	0.025	1 1/2	1/2	9 000	

### STANDARD TWIST KNOT HIGH SPEED STEEL SMALL GRINDER

- Works aggressively, smoothly and efficiently on air or portable power tools
- **Applications:** Cleans grooves, T-connections, weld beads and surface prep



Model No.	Brush Dia."	Arbor Hole	Colour	Wire Gauge"	Trim Length"	Max RPM	Price /Each
<b>STEEL</b>							
BX305	4	5/8"-11NC	Steel	0.02	7/8	20 000	
BX206	5	5/8"-11NC	Steel	0.02	1	12 000	
<b>STAINLESS</b>							
BX299	4	5/8"-11NC	Steel	0.02	7/8	20 000	
BX207	5	5/8"-11NC	Steel	0.02	1	12 000	

## WIRE WHEEL BRUSHES

- Narrow face for confined and hard to reach contact areas
- Low flex high impact aggressive brush action
- Perfect for expansion joints and filler welds
- For root and hot pass weld cleaning
- Customization available



Model No.	Brush Dia."	Face Width"	Fill Dia."	Arbor Size	Knot Type	No. of Knots	RPM	Price /Each
<b>STEEL</b>								
TT265	4	3/16	0.020	5/8"-11	Stringer	32	20 000	
TT271	4-7/8	3/16	0.020	5/8"-11	Stringer	48	12 500	
TC019	5-7/8	3/16	0.020	5/8"-11	Stringer	48	12 500	
NU438	4	1/2	0.020	5/8"-11	Standard	20	20 000	
NU440	6	1/2	0.014	5/8"-11	Standard	28	9 000	
NU442	8	5/8	0.014	5/8"-11	Standard	40	6 000	
<b>STAINLESS</b>								
TT270	4	3/16	0.020	5/8"-11	Stringer	32	20 000	
TT272	4-7/8	3/16	0.020	5/8"-11	Stringer	48	12 500	
TT273	5-7/8	3/16	0.020	5/8"-11	Stringer	48	12 500	
NU439	4	1/2	0.020	5/8"-11	Standard	20	20 000	
NU441	6	1/2	0.014	5/8"-11	Standard	28	9 000	
NU443	8	5/8	0.014	5/8"-11	Standard	40	6 000	