

EXIT SIGNS

- New easy click design allows for fast installation
- Single face or double face orientation
- Various mounting orientation (wall, side, ceiling)
- Ideal for use in offices, schools and warehouses

XI788



XI789



Model No.	Description	Price /Each
XI788	Ni-Cd 3.6V 1000mAh Battery	
XI789	Lead-Acid Battery (6 V 6 Ah), with Lights	

RUNNING MAN SIGN WITH SECURITY LIGHTS

- New easy click design allows for fast installation
 - Single face or double face orientation
 - Various mounting orientation (wall, side, ceiling)
 - Ideal for use in offices, schools and warehouses
 - 2 hours of emergency light duration
 - Lead-acid battery (6 V 6 Ah)
- Model No. XI790**
Price/Each \$



STELLA RUNNING MAN COMBO EXIT SIGNS

- Running Man models are supplied with 120/347 VAC dual input (hardwire)
- Push button test switch
- Self-powered for minimum 30 minutes – 6V DC 36W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 5-Watt tungsten heads
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Certified for sale in Canada by an accredited certification body



Model No. XE664
Mfg. No. SL-RM-6-36-L-U-0LR-M-2SR/9W
Price/Each \$

STELLA RUNNING MAN EXIT SIGNS

- Feature 120/347 VAC dual input (hardwire), universal DC, 6-24 VDC or self-powered
- Running Man sign uses a 2 watt LED source
- Long life LED light source
- Universal pictograms included showing left indicators, right indicators and no indicators
- 20-gauge steel construction with white baked powder coat paint finish
- Pre-stamped universal mounting and keyhole slots on backplate



XE662



Model No. XE662
Mfg. No. SL-RM-SP-L-U-0LR-M (Self-powered)
Price/Each \$

Model No. XE663
Mfg. No. SL-RM-L-U-0LR-M-UDC (6-24 VDC)
Price/Each \$



STELLA EXIT SIGNS

- C860 approved
- Standard 120/347VAC input (hardwire) and sealed nickel-cadmium batteries provide a minimum of 30 minutes of emergency duration
- Uses 2 W LED board
- Long life LED light source
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish
- Pre-stamped universal mounting and keyhole slots on backplate

XB930



XB933



Model No.	Mfg. No.	Description	Dimensions W" x D" x H"	Price /Each
XB930	SLE-SP-L-R-U-M	Exit	12 x 2.25 x 7.5	
XB933	SLS-L-R-U-M-UDC	Sortie	18.5 x 2.25 x 7.5	

STELLA COMBINATION SIGNS

- C860 approved
- LED EXIT and SORTIE models 120/277/347 VAC dual input (hard wire)
- Push button test switch
- Self-powered for minimum 30 minutes -6 VDC 36 W
- Solid state transfer charger
- Dual diagnostic LEDs indicate AC-ON and CHARGE
- Brownout and low voltage protection
- Two top mounted high impact thermoplastic PAR18 9 W tungsten heads
- Knockout chevrons
- 20-gauge steel construction with baked powder coat white paint finish



Model No.	Mfg. No.	Description	Price /Each
XB929	SLE-6-36-L-R-U-M-2SR/9W	Exit	
XB932	SLS-6-36-L-R-U-M-2SR/9W	Sortie	
REPLACEMENT BULB			
XB338	LP104	9 W Tungsten	